



Material Composition Declaration

© Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.

This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.

Adobe Reader version 7.0.5 is required to complete this declaration.

| | | | |
|-------------------|----------------------------------------------------------------------------------------------------------------------------|----------------------------------|---------------------------------------------------------------------------------------------|
| 1752-2 1.1 | IPC Web Site for Information on IPC-1752 Standard http://www.ipc.org/IPC-175x | Form Type * Distribute | Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Informat |
|-------------------|----------------------------------------------------------------------------------------------------------------------------|----------------------------------|---------------------------------------------------------------------------------------------|

Supplier Information

| | | | | | | | | |
|---------------------------------------------------------|-------------------------------------------|-----------------------------------------------|-----------------------------------------------------|-----------------------------------------------------|------------------------|-----------------|-----|-----------|
| Company Name * Cypress Semiconductor Corp | Company Unique ID CY | Unique ID Authority CY | Response Date * 2020-05-17 | Response Document ID | | | | |
| Contact Name * Quality Customer Support Gr | Title - Contact QA Customer Support | Phone - Contact * 6328497500 | Email - Contact * qacs_team@cypress.com | Duplicate Contact -> Authorized Representative | | | | |
| Authorized Representative * Jeff Gary Balleca | Title - Representative Staff EHS Engr. | Phone - Representative * 6328497500 | Email - Representative * jgtb@cypress.com | Supplier Comments or URL for Additional Information | | | | |
| Requester Item Number | Mfr Item Number | Mfr Item Name | Effective Date | Version | Manufacturing Site | Weight * | UOM | Unit Type |
| FBGA165_BB165_13 x 15 | FBGA165_BB165_13 x 15 mm | FBGA165_BB165_13 x 15 mm | 2020-05-17 | | ASEK | 568.71 | mg | Each |
| Alternate Recommendation | | | | Alternate Item Comments | Package QTP No. 052208 | | | |

Manufacturing Process Information

| | | | | | |
|----------------------------------------------------------------------|----------------------------------------|----------------------------------|-----------------------------------------------|---------------------------------------------------|-------------------------------------|
| Terminal Plating / Grid Array Material Tin/Lead (Sn63Pb37) | Terminal Base Alloy CU Alloy | J-STD-020 MSL Rating 3 | Peak Process Body Temperature 220 C | Max Time at Peak Temperature 20 seconds | Number of Reflow Cycles 3 |
|----------------------------------------------------------------------|----------------------------------------|----------------------------------|-----------------------------------------------|---------------------------------------------------|-------------------------------------|

Comments
TEST REPORTS: MC (001-79853); DA (001-79607) ; PLATING (002-26565); BW (001-79685) ; SUB (002-12811)

Save the fields in this form to a file

Export Data

Import fields from a file into this form

Import Data

Clear all of the fields on this form

Reset Form

Lock the fields on this form to prevent changes

Lock Supplier Fields

RoHS Material Composition Declaration

Declaration Type *

Detailed

RoHS Directive
2002/95/EC

RoHS Definition: Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury, Hexavalent Chromium, Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE) and quantity limit of 0.01% by mass (100 PPM) of homogeneous material for Cadmium

Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2002/95/EC and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance in excess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.

RoHS Declaration *

3 - Item(s) does not contain RoHS restricted substances per the definition above except for lead in solders and selected exemptions, if any

Supplier Acceptance *

Accepted

Exemptions: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.

Exemption List Version

EL-2006/690/EC

+

-

7b. Lead in solders for servers, storage and storage array systems, network infrastructure equipment for switching, signalling, transmission as well as network management for telecommunications.

Declaration Signature

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

| | | Item/SubItem Name | | Homogeneous Material | | Weight | Unit of Measure | Level | | Substance Category | | Substance | | CAS | Exempt | Weight | Unit of Measure | Tolerance | | PPM | | |
|----|----|-------------------|--|----------------------|----|------------------|-----------------|-------|----|--------------------|----------|-------------------------|----|-----|----------------------|-------------|-----------------|-----------|----|-----|--|--------|
| | | | | | | | | | | | | | | | | | | - | + | | | |
| +I | -I | Substrate | | +M | -M | Base Material | 161.2 | mg | +C | -C | Supplier | SiO2 | +S | -S | SiO2 | 60676-86-0 | | 16.91 | mg | | | 29,734 |
| | | | | | | | | | +C | -C | Supplier | Acrylic | +S | -S | Acrylic | Trade Secre | | 14.83 | mg | | | 26,077 |
| | | | | | | | | | +C | -C | Supplier | Epoxy | +S | -S | Epoxy | 29690-82-2, | | 9.9 | mg | | | 17,408 |
| | | | | | | | | | +C | -C | Supplier | Bisphenol | +S | -S | Bisphenol | 13676-54-5 | | 24.15 | mg | | | 42,465 |
| | | | | | | | | | +C | -C | Supplier | Triazol | +S | -S | Triazol | 25722-66-1 | | 28.98 | mg | | | 50,957 |
| | | | | | | | | | +C | -C | Supplier | Cu | +S | -S | Cu | 7440-50-8 | | 63.4 | mg | | | 111,48 |
| | | | | | | | | | +C | -C | B | Nickel (external applic | +S | -S | Nickel | 7440-02-0 | | 2.24 | mg | | | 3,939 |
| | | | | | | | | | +C | -C | Supplier | Au | +S | -S | Au | 7440-57-5 | | 0.79 | mg | | | 1,389 |
| +I | -I | Solder Ball | | +M | -M | External Plating | 79.26 | mg | +C | -C | Supplier | Sn | +S | -S | Sn | 7440-31-5 | | 49.93 | mg | | | 87,795 |
| | | | | | | | | | +C | -C | A | Lead/Lead Compound | +S | -S | Lead | 7439-92-1 | | 29.33 | mg | | | 51,573 |
| +I | -I | Die Attach | | +M | -M | Adhesive | 42.82 | mg | +C | -C | Supplier | Silver | +S | -S | Silver | 7440-22-4 | | 32.97 | mg | | | 57,973 |
| | | | | | | | | | +C | -C | Supplier | Epoxy Resin | +S | -S | Epoxy Resin | Trade Secre | | 2.25 | mg | | | 3,956 |
| | | | | | | | | | +C | -C | Supplier | Functionalized Ester | +S | -S | Functionalized Ester | Trade Secre | | 2.25 | mg | | | 3,956 |
| | | | | | | | | | +C | -C | Supplier | Diester | +S | -S | Diester | Trade Secre | | 5.35 | mg | | | 9,407 |
| +I | -I | Die | | +M | -M | Circuit | 25.25 | mg | +C | -C | Supplier | Si | +S | -S | Si | 7440-21-3 | | 25.25 | mg | | | 44,399 |
| +I | -I | Wire | | +M | -M | Interconnect | 3.56 | mg | +C | -C | Supplier | Gold (Au) | +S | -S | Gold (Au) | 7440-57-5 | | 3.56 | mg | | | 6,260 |
| +I | -I | Mold Compound | | +M | -M | Encapsulation | 256.62 | mg | +C | -C | Supplier | Silica fused | +S | -S | Silica fused | 60676-86-0 | | 228.39 | mg | | | 401,59 |
| | | | | | | | | | +C | -C | Supplier | Epoxy Resin 1 | +S | -S | Epoxy Resin 1 | 93705-66-9 | | 11.55 | mg | | | 20,309 |
| | | | | | | | | | +C | -C | Supplier | Epoxy Resin 2 | +S | -S | Epoxy Resin 2 | Trade Secre | | 5.13 | mg | | | 9,020 |
| | | | | | | | | | +C | -C | Supplier | Phenol resin | +S | -S | Phenol resin | 106466-55-1 | | 11.55 | mg | | | 20,309 |