


ModusToolbox software is a set of tools that support Cypress device configuration and application development. These tools enable you to integrate Cypress devices into your existing development methodology.

This guide provides a quick walkthrough for using the Eclipse IDE provided as part of ModusToolbox. If you wish to use other IDEs, such as VS Code, IAR, or µVision, refer to the “Export to IDEs” chapter in the [ModusToolbox User Guide](#).

Download/Install ModusToolbox and Run Eclipse IDE

Refer to the instructions in the [ModusToolbox Installation Guide](#). After you accept the License Agreement, the Eclipse IDE opens a dialog to specify the workspace. Then, it opens with an empty Project Explorer by default.



This guide focuses on these areas of the Eclipse IDE:


- The **Project Explorer** contains the application folders and files.
- The **Quick Panel** provides links to tool commands and documentation.
- The **Console** displays various messages when updating the application in some way (building, programming, etc.)

Create New Application


Creating an application includes several steps, as follows:

Step 1: Open Project Creator Tool


In the **Quick Panel**, click the “New Application” link.



Or, select **File > New > ModusToolbox Application**.




The Eclipse IDE displays a message and waits for the Project Creator tool to open.



Step 2: Choose Board Support Package (BSP)


When the Project Creator tool opens, click on the **Kit Name**; see the description for it on the right. For this example, select the **CY8CKIT-062-WIFI-BT** kit. The following image is an example; the precise list of boards available in this version of ModusToolbox will reflect the platforms available for development.



Step 3: Select Application

Click **Next >** to open the Select Application page. This page displays example applications, which demonstrate different features available on the selected BSP. In this case, the CY8CKIT-062-WIFI-BT provides the PSoc 62 MCU and the CYW4343W WiFi + Bluetooth Combo Chip. You can create examples for PSoc 6 MCU resources such as CapSense and QSPI, as well as numerous examples for AnyCloud connectivity.

For this example, select **Hello World** from the list. This example exercises the PSoc 6 MCU to blink an LED.




Note The actual application names available might vary.

Type a name for your application or leave the default name. Do not use spaces in the application name. Also, do not use common illegal characters, such as:

* . " \ / \ [] : ; | = ,


Step 4: Create Application

Click **Create** to start creating the application. The tool displays various messages.




When the process completes, a message states that the application was created, and the Project Creator tool closes automatically.

Then, the IDE displays a message that the project is being imported.




After several moments, the application opens with the *Hello_World* project in the Project Explorer, and the *README.md* file opens in the file viewer.



Add/Modify Application Code

Code example applications work as they are, and there is no need to add or modify code in order to build or program them. However, if you want to update and change the application to do something else, open the appropriate file in the code editor.


Double-click the *main.c* file to open it.



As you type into the file, an asterisk (*) will appear in the file's tab to indicate changes were made. The **Save/Save As** commands will also become available to select.

View Device Resources

To view peripherals, pins, clocks, etc., open the Device Configurator. Right-click on the project folder and select **ModusToolbox > Device Configurator 2.20**.



The Device Configurator provides access to the BSP resources and settings. Each enabled resource contains one or more links to the related API documentation. There are also buttons to open other configurators for CapSense®, QSPI, Smart I/O™, etc.

Note If you make changes to settings in any of these configurators, you are making changes to a standard BSP library, which will cause the repo to become dirty. Additionally, if the BSP is in the shared asset repository, changes will impact all applications that use the shared BSP. If you wish to make changes, you should first copy the configuration information to the application and override the BSP configuration or create a custom BSP. For more information, refer to the [ModusToolbox User Guide](#).


Note The Device Configurator cannot be used to open Library Configurators, such as Bluetooth and USB.

For more information, refer to the [Device Configurator Guide](#), which is also available by selecting **View Help** from the tool's **Help** menu.


Build the Application

Building the application is not specifically required, because building will be performed as part of the programming and debugging process. However, if you are running the Eclipse IDE without any hardware attached, you may wish to build your application to ensure all the code is correct.

In the **Quick Panel**, click the “Build Hello_World Application” link. Build information will display in the Console pane.



If you have the *Hello_World* project selected, you can also select **Build Project** from the **Project** menu or from the right-click menu. The Eclipse menus change based on what you have selected in the Project Explorer.



Program the Device

There are several different “Launch Configurations” for programming and debugging the various development kits and starter applications within the Eclipse IDE. These Launch Configurations provide details about how to configure the application. This section provides a brief walkthrough for programming this example. For more details about other Launch Configurations and settings, refer to the [Eclipse IDE for ModusToolbox User Guide](#), “Program and Debug” chapter.


Connect the Kit

Follow the instructions provided with the CY8CKIT-062-WIFI-BT kit to connect it to the PC with the USB cable.


Note This kit’s firmware may be set to KitProg2. To use this kit with the ModusToolbox software, you must upgrade the firmware to KitProg3. Refer to the [KitProg3 User Guide](#) for more details.

Program

In the Project Explorer, select the *Hello_World* application. Then, in the **Quick Panel**, click the “Hello_World Program (KitProg3_MiniProg4)” link.




If needed, the IDE builds the application and messages display in the Console. If the build is successful, device programming starts immediately. If there are build errors, then error messages will indicate as such. When complete, the LED will start blinking.




Debug the Program

As mentioned under the [Program the Device](#) section in this document, there are many different Launch Configurations for different kits and applications. This section provides a brief walkthrough for debugging this example. For more details about other Launch Configurations and settings, refer to the [Eclipse IDE for ModusToolbox User Guide](#), “Program and Debug” chapter.

In the Project Explorer, select the *Hello_World* application. Then, in the **Quick Panel**, click the “Hello_World Debug (KitProg3)” link under **Launches**.



If needed, the IDE builds the application and messages display in the Console. If the build is successful, the IDE switches to debug mode automatically. If there are build errors, then error messages will indicate as such.



Next Steps

For more information about the Eclipse IDE, refer to the following:

- [Eclipse IDE for ModusToolbox User Guide](#) – This provides more details about features added to the ModusToolbox version of the Eclipse IDE.
- [Eclipse IDE Survival Guide](#) – This provides a FAQ about how to use Eclipse to perform common tasks.
- [Eclipse Workbench User Guide](#) – This provides more details about the generic Eclipse environment.

For more information about ModusToolbox software, refer to the [ModusToolbox User Guide](#).

© Cypress Semiconductor Corporation, 2017-2020. This document is the property of Cypress Semiconductor Corporation and its subsidiaries, including Spansion LLC ("Cypress"). This document, including any software or firmware included or referenced in this document ("Software"), is owned by Cypress under the intellectual property laws and treaties of the United States and other countries worldwide. Cypress reserves all rights under such laws and treaties and does not, except as specifically stated in this paragraph, grant any license under its patents, copyrights, trademarks, or other intellectual property rights. If the Software is not accompanied by a license agreement and you do not otherwise have a written agreement with Cypress governing the use of the Software, then Cypress hereby grants you a personal, non-exclusive, nontransferable license (without the right to sublicense) (1) under its copyright rights in the Software (a) for Software provided in source code form, to modify and reproduce the Software solely for use with Cypress hardware products, only internally within your organization, and (b) to distribute the Software in binary code form externally to end users (either directly or indirectly through resellers and distributors), solely for use on Cypress hardware product units, and (2) under those claims of Cypress's patents that are infringed by the Software (as provided by Cypress, unmodified) to make, use, distribute, and import the Software solely for use with Cypress hardware products. Any other use, reproduction, modification, translation, or compilation of the Software is prohibited.

TO THE EXTENT PERMITTED BY APPLICABLE LAW, CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS DOCUMENT OR ANY SOFTWARE OR ACCOMPANYING HARDWARE, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. To the extent permitted by applicable law, Cypress reserves the right to make changes to this document without further notice. Cypress does not assume any liability arising out of the application or use of any product or circuit described in this document. Any information provided in this document, including any sample design information or programming code, is provided only for reference purposes. It is the responsibility of the user of this document to properly design, program, and test the functionality and safety of any application made of this information and any resulting product. Cypress products are not designed, intended, or authorized for use as critical components in systems designed or intended for the operation of weapons, weapons systems, nuclear installations, life-support devices or systems, other medical devices or systems (including resuscitation equipment and surgical implants), pollution control or hazardous substances management, or other uses where the failure of the device or system could cause personal injury, death, or property damage ("Unintended Uses"). A critical component is any component of a device or system whose failure to perform can be reasonably expected to cause the failure of the device or system, or to affect its safety or effectiveness. Cypress is not liable, in whole or in part, and you shall and hereby do release Cypress from any claim, damage, or other liability arising from or related to all Unintended Uses of Cypress products. You shall indemnify and hold Cypress harmless from and against all claims, costs, damages, and other liabilities, including claims for personal injury or death, arising from or related to any Unintended Uses of Cypress products.

Cypress, the Cypress logo, Spansion, the Spansion logo, and combinations thereof, ModusToolbox, WICED, PSoC, CapSense, EZ-USB, F-RAM, and Traveo are trademarks or registered trademarks of Cypress in the United States and other countries. For a more complete list of Cypress trademarks, visit cypress.com. Other names and brands may be claimed as property of their respective owners.